



Homeowners invest in Celect® Cellect Composite Siding for maximum curb appeal and minimal maintenance.

HERE'S HOW TO KEEP CELECT AT ITS BEST.

CLEANING DOS:

- Test any cleaning solution or method on a small, inconspicuous area of the siding to prevent damage.
- Use a clean, soft cotton cloth when necessary and frequently replace the cloth to avoid scratching the finish.
- For regular, general washing: Mild detergents such as Dawn[®] and Murphy[®] Oil Soap, are suggested.
- For small spot cleaning, it is safe to use Windex®, mild detergents, or isopropyl alcohol, but avoid scrubbing the same spot repeatedly as this could soften or damage the finish. Apply any acceptable cleaning solution to the surface of the siding using a standard pump spray bottle, then rinse with a garden hose.
- The finish on Celect is resistant to mildew. However, should mildew occur, add standard laundry bleach to your cleaning solution at a ratio of 1 part bleach to 10 parts water (13 ounces per gallon).

CLEANING DON'TS:

- Avoid using solvents such as nail polish remover, acetone, MEK and butyl CARBITOL™. These chemicals will damage the finish.
- Avoid using bleach or cleaners that contain bleach, such as Clorox®
 Clean-Up®, as these cleaners may permanently discolor the finish.
- Steer clear of cleaners that contain any kind of abrasives, such as Soft Scrub[®], as they may scratch the finish. Avoid using scrub brushes.
- Most dirt and spots can be removed easily and safely with the suggested methods and a water hose. Pressure washing even at a low setting is usually not needed.







SIDING & ACCESSORIES TRIM & MOULDINGS ROOFING STONE WINDOWS OUTDOOR LIVING





